

Light is flat

OSRAM UltraFlat-System

Your design visions become reality


With a depth of just 11 mm, our UltraFlat DALI LED driver teams up perfectly with the PrevaLED® Linear Slim LED module and the small OSRAM UltraFlat light and motion sensor enabling you to realize luminaire designs that were not possible before.

Light is OSRAM

OSRAM

Experience a new era in creative luminaire design!

An ultraflat DALI LED driver, the OSRAM UltraFlat light and motion sensor perfectly coordinated with it and the extra slim LED module PrevaLED® Linear Slim: The innovative OSRAM UltraFlat-System will enable you to create unique, design-oriented luminaires with an effective installation depth of just 11 mm.



The OSRAM UltraFlat-System: unparalleled freedom in design – with the highest level of efficiency and perfect interaction

No matter what you may have in mind: You can turn your vision into reality with the help of the new and innovative OSRAM UltraFlat-System. With their ultraflat drivers, sensors and the large choice of LED modules that come in different light colors and lengths, this OSRAM system solution offers just about every feature that creative luminaire producers and lighting planners can dream of. You can profit from a casing height of just 11 mm – and from the unsurpassed design freedom it creates.




OSRAM OPTOTRONIC® UltraFlat DALI LED driver:

- Incomparable casing height of just 11 mm
- 50 % flatter than standard OTi® DALI – with optimized performance and functionality
- An array of programming interfaces: DALI, LEDset2, NFC
- Low current ripple: less than 1 %
- Very high efficiency: up to 93 %
- Low standby consumption
- Lifetime: 50,000 hours (at Tc max)
- Analog, continuously dimmable light of 1% to 100 %
- According to DALI 2 standard
- Complete product family with uniform design and layout
- Intelligent features like Fit for Smart Grid, Touch DIM function, corridor function, Fit for Emergency included



OSRAM light and motion sensors:

- Extremely small: 50×20×11 mm
- Lifetime: 50,000 hours (at Tc max)
- Detection range*: motion ≤6×6 m, presence ≤4×4 m
- Touch DIM version for smart individual luminaires
- DALI version for integration into DALI control systems



OSRAM PrevaLED® Linear Slim:

- 20 mm LED module with high luminous efficacy: up to 173 lm/W
- Wide selection of light colors from 3,000 K to 6,500 K and color rendering of >80, >90
- A large range of module lengths: 140, 280, 560 and 1,400 mm
- High homogeneity thanks to low LED pitch



* For 3 m installation heights

Innovation and quality are part of a system at our company

From LED drivers and LED modules to light management systems – everything comes from a single source and from a leading brand on which you can rely at any time and in any situation.

OSRAM's complete LED system solutions: for every luminaire, every application and every application area with a system guarantee*

We provide you with reliable, easily integrated and user friendly hardware and software that you can use to successfully perform all of your LED projects. On request, we are also able to develop customized module solutions for you.

* You will find more details about the OSRAM guarantee at www.osram.com/corporate/home/services/guarantees

One click will take you to an individual light solution: www.osram.com/tailormade





OSRAM OPTOTRONIC® UltraFlat DALI LED driver

| Product name | Product code | Line voltage AC | Input voltage DC | Nominal output voltage | Nominal output current | Nominal output power | Ambient temperature range |
|--------------------------------------|---------------|-----------------|------------------|------------------------|------------------------|----------------------|---------------------------|
| OTi DALI 35/220...240/400 D LT2 UF L | 4052899957022 | 198...264 V | 176...276 V | 54...240 V | 75...400 mA | 4...38 W | -25...+60 °C |
| OTi DALI 75/220...240/700 D LT2 UF L | 4052899957046 | 198...264 V | 176...276 V | 54...240 V | 75...700 mA | 9,7...75 W | -25...+50 °C |



OSRAM UltraFlat light and motion sensors


| Product name | Product code | Motion detection range* | Presence detection range* | Light sensing range | Installation type | Protection class | Ambient temperature range |
|------------------|---------------|-------------------------|---------------------------|---------------------|------------------------|------------------|---------------------------|
| LS/PD LT2 LI UF | 4052899984615 | 6 × 6 m | 4 × 4 m | 10...1,000 lx | Luminaire installation | IP 20 | 0...+50 °C |
| LS/PD DALI LI UF | 4052899984608 | 6 × 6 m | 4 × 4 m | 10...1,000 lx | Luminaire installation | IP 20 | 0...+50 °C |

* For 3 m installation heights



OSRAM PrevaLED® Linear Slim (portfolio excerpt, construction length 560 mm)


| Product name | Product code | Nominal wattage | Color temperature | Total useful luminous flux | Module efficacy | Nom. useful luminous flux 120° | Color rendering index R _a |
|--------------------------|---------------|-----------------|-------------------|----------------------------|-----------------|--------------------------------|--------------------------------------|
| PL-LIN S-Z3 4000-830 560 | 4052899347144 | 23.10 W | 3,000 K | 4,000 lm | 150 lm/W | 4,000 lm | >80 |
| PL-LIN S-Z3 4000-840 560 | 4052899347168 | 23.10 W | 4,000 K | 4,000 lm | 169 lm/W | 4,000 lm | >80 |
| PL-LIN S-Z3 4000-865 560 | 4052899347182 | 23.10 W | 6,500 K | 4,000 lm | 163 lm/W | 4,000 lm | >80 |



Discover OSRAM's LED system solutions for offices, hotels and industry in an attractive, informative and innovative way at systemsolution.osram.com

You will find more information about us and our wide product range at:

OSRAM Digital Lighting Systems
www.osram.com/ds

Follow OSRAM Digital Lighting Systems @ 

OSRAM GmbH

Head office

Marcel-Breuer-Strasse 6
 80807 Munich, Germany
 Phone +49 89 6213-0
 Fax +49 89 6213-2020
www.osram.com

